

Christie MicroTiles LED

Indoor LED tiles




Technical specification		1.0mm (Series 80)	0.75mm (Series 60)	
Display technology	pixel pitch	• 1.0mm	• 0.75mm	
	pixel configuration	• 3 LED diodes in 1 package (1R1G1B)	• 4 pixels in 1 package (4R4G4B)	
	pixel density	• 1,000,000 pixels/m ²	• 1,780,000 pixels/m ²	
	maximum calibrated brightness	• 2000 (TBC) nits (cd/m ²)		
	aspect ratio	• 8:09		
	contrast ratio (full field)	• Greater than 5000:1		
	viewing angle	• 160° H, 140° V		
	refresh rate	• Up to 3840 Hz		
	scan rate	• 1/15	• 1/60	
	color temperature	• 2700-9600K		
	display colors	• 208 trillion (18-bit)		
	color space	• Typical 98% P3		
	LED lifespan (50% brightness)	• 100,000 hours		
	runtime	• 24/7		
	Signal	inputs	• E1000: 2 x HDMI 2.0 (HDCP), 2 x DisplayPort 1.2 (HDCP)	
		outputs	• 2 x QSFP+ (Bi-directional)	
control		• 1 x RJ45 Ethernet, USB (RS232 via dongle)		
Power	power input rating	• 100-240 VAC @ 50/60 Hz - remote power supply ¹ • 48-56 VDC • 48V Power over Ethernet - per tile		
	power consumption	• 20W typical, 50W maximum - per tile (TBC)		
	heat output per tile	• 68 BTU/hr typical 170 BTU/hr maximum (TBC)		
Environment	operating temperature	• 32-104F (0-40C)		
	operating humidity	• 10-90% RH non-condensing		
	storage temperature	• 14-122F (-10-55C)		
	environment	• Indoor		
	IP rating	• 30		
Physical	tile dimensions (installed)	• (W x H x D) 9.45 x 10.63 x 3.35" (240 x 270 x 85mm)		
	tile diagonal	• 14.22" (361mm)		
	tile area	• 0.70ft ² (0.0648m ²)		
	tile resolution	• 240 x 270	• 320 x 360	
	tile weight	• 4.85lbs (2.2kg) per tile • 74.85lbs (34.0kg) per square meter • Total installed weight (including proprietary QuickMount™ system) • 7.06lbs (3.2kg) per tile, 108.95lbs (49.4kg) per square meter		
	tile array size to achieve 1920 x 1080	• 8 x 4	• 6 x 3	
	tile design	• Die-cast aluminum		
	orientation	• Portrait (8:9) • Landscape (16:9)		
	service access	• All service from front		
	module dimensions	• (W x H) 9.45 x 3.54" (240 x 90mm)		
	module resolution	• 240 x 90	• 320 x 120	
	installation options	• Flat • Concave • Convex • 90 degree outside and inside corner • Hanging/flying • Creative shapes		
	direct mount system	• QuickMount system included - mounting plates, mounting template, wall anchors		
	additional required components	• Remote power supply rack shelf • Power supply unit modules (rectifiers) • Tile controller (Octroller), and wall controller sold separately		
	Certifications ²	• UL60950, FCC, CE, EMC, RoHS, RC2		
	Warranty	• Three years parts and labor limited warranty, extended warranty option available for a one-time fee at time of purchase		

Octroller

Signal	
inputs	• 2 x QSFP+ (Bi-directional)
outputs	• 8 X RJ45 Ethernet (PoE up to 75W per port)
control	• 1 x RJ45 Ethernet
Power	
power input rating	• 48-56 VDC
power consumption	• 600W maximum
Environment	
operating temperature	• 32-104F (0-40C)
operating humidity	• 10-90% RH non-condensing
storage temperature	• 14-122F (-10-55C)
environment	• Indoor

QuickMount system

Proprietary QuickMount system includes custom mounting templates, laser-cut steel mounting sheets and machined wall anchors to eliminate any alignment challenges, reducing time and cost.



¹ See remote power specifications for full details.

² Certain of the listed certifications may be pending and not yet issued. For the current status of the listed certifications, please contact an authorized Christie representative.

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

For the most current specification information, please visit christiedigital.com

Copyright 2022 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD3268-MicroTilesLED- 0.75-1mm-Datasheet-updates-Feb-23-EN

